## NSN 5340-01-297-2802

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-297-2802

Mounting Hole Type:
Plain and threaded
First Leg Length:
1.750 inches
Second Leg Length:
5.000 inches
Second Leg Width:
33.250 inches
First Leg Hole Diameter:
0.375 inches
Second Leg Hole Diameter:
0.438 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
Between 15.922 inches and 15.952 inches
Second Leg Distance Between Second And Third Hole Centers Along Width:
15.000 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.750 inches
Second Leg Distance From Edge To Hole Center Along Length:
1.500 inches
First Leg Thickness:
0.250 inches
Second Leg Thickness:
0.250 inches
First Leg Width:
33.250 inches
First Leg Distance Between First And Second Hole Centers Along Width:
15.937 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
15.000 inches
First Leg Distance From Edge To Hole Center Along Width:
0.750 inches
First Leg Distance From Edge To Hole Center Along Length:
0.750 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Three holes
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Three holes

## NSN 5340-01-297-2802

Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Special Features:
Gthree thd holes in first leg 0.375-24unf-2b; one arc shaped notch in first leg 1.500 in. Radius spaced 5.000 in. From end to arc center; arc
1.000 in. Dp from edge; bend radius 0.375 in.; color white
Material:
Steel comp 1020
Material Specification:
Qq-s-635, cond a federal specification single material response
Surface Treatment:
Enamel
Surface Treatment Specification:
Tt-e-489 federal specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A042a0