

View Online at <https://aerobasegroup.com/nsn/5340-01-297-4094>

Mounting Hole Type:

Plain and threaded

First Leg Length:

5.562 inches

Second Leg Length:

9.188 inches

Second Leg Width:

10.500 inches

First Leg Hole Diameter:

0.438 inches

Second Leg Hole Diameter:

0.375 inches

Second Leg Distance Between Hole Centers Along Width:

9.000 inches

Second Leg Distance Between Hole Centers Along Length:

4.984 mils and 5.016 centimeters

Second Leg Distance From Edge To Hole Center Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.750 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

10.500 inches

First Leg Distance Between Hole Centers Along Width:

Between 8.984 inches and 9.016 inches

First Leg Distance Between Hole Centers Along Length:

Between 2.984 inches and 3.016 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

0.375-24 unf-2b threaded holes four places second leg

Material:

Steel comp 1020

Material Specification:

Qq-s-635 federal specification single material response

Surface Treatment:

Enamel

Surface Treatment Specification:

Tt-e-489 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0