

View Online at <https://aerobasegroup.com/nsn/5340-01-297-4095>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.125 inches

**Second Leg Length:**

2.500 inches

**Second Leg Width:**

8.188 inches

**First Leg Hole Diameter:**

0.438 inches

**Second Leg Hole Diameter:**

0.312 inches

**Second Leg Distance Between Hole Centers Along Width:**

7.312 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

Between 3.109 inches and 3.141 inches

**Second Leg Distance Between Second And Third Hole Centers Along Width:**

1.062 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.438 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.938 inches

**First Leg Thickness:**

0.132 inches

**Second Leg Thickness:**

0.132 inches

**First Leg Width:**

8.188 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 5.546 inches and 5.578 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.312 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.563 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Two additional holes on second leg 0.312 in. Dia

**Material:**

Steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

**Material Specification:**

Qq-s-640, temper 2 to 5 federal specification all material responses

**Surface Treatment:**

Phosphate manganese

**Surface Treatment Specification:**

Mil-p-16232, type m, class 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-p-16232 spec.