

View Online at <https://aerobasegroup.com/nsn/5340-01-297-4095>

Mounting Hole Type:

Plain

First Leg Length:

1.125 inches

Second Leg Length:

2.500 inches

Second Leg Width:

8.188 inches

First Leg Hole Diameter:

0.438 inches

Second Leg Hole Diameter:

0.312 inches

Second Leg Distance Between Hole Centers Along Width:

7.312 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

Between 3.109 inches and 3.141 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

1.062 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.438 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.938 inches

First Leg Thickness:

0.132 inches

Second Leg Thickness:

0.132 inches

First Leg Width:

8.188 inches

First Leg Distance Between Hole Centers Along Width:

Between 5.546 inches and 5.578 inches

First Leg Distance From Edge To Hole Center Along Width:

1.312 inches

First Leg Distance From Edge To Hole Center Along Length:

0.563 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Two additional holes on second leg 0.312 in. Dia

Material:

Steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

Material Specification:

Qq-s-640, temper 2 to 5 federal specification all material responses

Surface Treatment:

Phosphate manganese

Surface Treatment Specification:

Mil-p-16232, type m, class 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-p-16232 spec.