NSN 5340-01-297-6353

Mounting Bracket - Page 1 of 1

A042a0



View Online at https://aerobasegroup.com/nsn/5340-01-297-6353

End Application:
H-60 helicopters
Special Features:
$4.220 \; in. Lg, furn w/two slots, two holes 0.3125 in. Min, 0.3130 in. Maximum dia, two holes 0.128 in. Min, 0.132 in. Maximum dia; \; furn w/two slots, two holes 0.3125 in. Min, 0.3130 in. Maximum dia, two holes 0.128 in. Min, 0.132 in. Maximum dia; \; furn w/two slots, two holes 0.3125 in. Min, 0.3130 in. Maximum dia, two holes 0.128 in. Min, 0.132 in. Maximum dia; \; furn w/two slots, two holes 0.3125 in. Min, 0.3130 in. Maximum dia, two holes 0.128 in. Min, 0.132 in. Maximum dia; \; furn w/two slots, two holes 0.3125 in. Min, 0.3130 in. Maximum dia, two holes 0.128 in. Min, 0.132 in. Maximum dia; \; furn w/two slots, two holes 0.128 in. Min, 0.132 in. Maximum dia; \; furn w/two slots, two holes 0.128 in. Min, 0.132 in. Maximum dia; \; furn w/two slots, two holes 0.128 in. Min, 0.132 in. Maximum dia; \; furn w/two slots, two holes 0.128 in. Min, 0.132 in. Min, 0.13$
w/anchor nut and rivet
Material:
Cobalt comp I-605
Material Specification:
07482-b50tf144 mfr ref single material response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: