

View Online at <https://aerobasegroup.com/nsn/5340-01-298-1320>

Mounting Hole Type:

Plain

First Leg Length:

2.000 inches

Second Leg Length:

2.005 inches

Second Leg Width:

39.750 inches

First Leg Hole Diameter:

0.413 mils and 0.416 centimeters

Second Leg Hole Diameter:

0.358 inches

Second Leg Distance Between Hole Centers Along Width:

38.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.880 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.943 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Height:

2.750 inches

Center Section Width:

39.750 inches

Center Section Thickness:

0.125 inches

First Leg Width:

39.750 inches

First Leg End Width:

38.000 inches

First Leg Distance Between Hole Centers Along Width:

22.000 inches

First Leg Distance From Edge To Hole Center Along Width:

2.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.938 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Color white, no. 17925, per fed, std 595

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, temper h32 federal specification single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-83286, type 1 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-83286 spec.