

View Online at <https://aerobasegroup.com/nsn/5340-01-298-4860>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.560 inches

**Second Leg Length:**

3.120 inches

**Second Leg Width:**

3.380 inches

**Second Leg End Width:**

0.250 inches

**First Leg Slot Length:**

0.703 inches

**First Leg Slot Width:**

0.453 inches

**Second Leg Hole Diameter:**

Between 0.190 inches and 0.201 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.620 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.120 inches

**First Leg Thickness:**

0.190 inches

**Second Leg Thickness:**

0.190 inches

**First Leg Width:**

3.380 inches

**First Leg End Width:**

3.140 inches

**First Leg Distance Between Hole Centers Along Width:**

1.950 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.691 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.566 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Angle

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

110.0 degrees

**First Leg Chamfer Angle:**

45.0 degrees

**Special Features:**

Includes one plate, p/n 12369712-2, located on second leg, perpendicular to the width of the bracket

**Material:**

Aluminum alloy 5083 or aluminum alloy 5086

**Material Specification:**

Qq-a-250/6 h321 or h323 federal specification 1st material response or qq-a-250/7 h32 federal specification 2nd material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 cl 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.