

View Online at <https://aerobasegroup.com/nsn/5340-01-298-4860>

Mounting Hole Type:

Plain

First Leg Length:

1.560 inches

Second Leg Length:

3.120 inches

Second Leg Width:

3.380 inches

Second Leg End Width:

0.250 inches

First Leg Slot Length:

0.703 inches

First Leg Slot Width:

0.453 inches

Second Leg Hole Diameter:

Between 0.190 inches and 0.201 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.620 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.120 inches

First Leg Thickness:

0.190 inches

Second Leg Thickness:

0.190 inches

First Leg Width:

3.380 inches

First Leg End Width:

3.140 inches

First Leg Distance Between Hole Centers Along Width:

1.950 inches

First Leg Distance From Edge To Hole Center Along Width:

0.691 inches

First Leg Distance From Edge To Hole Center Along Length:

0.566 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Angle

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

110.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Special Features:

Includes one plate, p/n 12369712-2, located on second leg, perpendicular to the width of the bracket

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-250/6 h321 or h323 federal specification 1st material response or qq-a-250/7 h32 federal specification 2nd material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.