NSN 5340-01-298-7626

Swivel Caster - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-298-7626

| · |
|--|
| Center To Center Distance Between Bolt Holes Along Width: |
| 7.000 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 9.750 inches |
| End Application: |
| P/n 68d291333-1001; f15e |
| Wheel Quantity: |
| 2 |
| Safe Operating Load Rating: |
| 2080.0 pounds |
| Material And Location: |
| Steel |
| Surface Treatment And Location: |
| Cadmium plated or zinc plated |
| Wheel Type: |
| Pneumatic tire |
| Wheel Diameter: |
| 14.880 inches |
| Effective Height: |
| 19.938 inches |
| Features Provided: |
| Swivel lock |
| Plate Style: |
| Rectangular |
| Swivel Bearing Type: |
| Thrust |
| Tread Width: |
| 4.000 inches |
| Caster Plate Length: |
| 11.000 inches |
| Caster Plate Width: |
| 9.000 inches |
| Caster Plate Mounting Hole Diameter: |
| 0.654 inches |
| Special Features: |
| Aft side |
| Style Designator: |
| Swivel nonoffset |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 5340-01-298-7626

Swivel Caster - Page 2 of 2



Demilitarization:

No

Fiig:

A25600