

View Online at <https://aerobasegroup.com/nsn/5340-01-299-5943>

Cross Sectional Shape:

Flat

Width:

8.000 inches

Edge Shape:

Rectangle, multi holes

Length:

21.470 inches

Corner Radius:

0.120 inches

Hole Quantity Along Length:

12

Hole Quantity Along Width:

9

Distance Between Holes Along Length:

3.031 inches and 2.625 inches and 3.375 inches and 2.937 inches

Distance Between Holes Along Width:

2.250 inches and 3.000 inches

Distance From First Hole Centerline To End Along Length:

0.220 inches

Distance From First Hole Centerline To End Along Width:

0.250 inches

Body Thickness:

1.900 inches

Securing Device Type:

Threaded fastener

Mounting Opening Shape Style:

Threaded hole

End Application:

Alq-135b countermeasure

Features Provided:

Special marking

Special Features:

Hole legend: a-e, 'a' diameter requires 0.138-32 unc 2b thd and is cbored 0.312 in., 'b' diameter 0.1885 to 0.1895 in. Thru, 'c' diameter is 0.103 to 0.105 in. & cbored 0.187 in. X 0.093 in. Dp; 'd' diameter is 0.1885 to 0.1895 in. & 0.156 dp, 'e' diameter is 0.220 in. & 0.156 in. Dp; item requires a cover frame p/n 151-002434-102, 3 locating bushings p/n 151-002434-103, bushings are of stainless steel cl 303, cond a per astm a 582 & passivated (e300) per mil-f-14072; also required is 6 fin stock of aluminum alloy 1100-0, qq-a-250/1, 0.006 in. Thk p/n 151-002434-104, & 2 bosses p/n 151-002434-105 boss lg 0.620 in., & 0.070 to 0.080 in. Thk

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/8 federal specification single material response or qq-a-250/11 federal specification single material response

Surface Treatment:

Primer and paint polyurethane

Surface Treatment Specification:

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-p-23377 spec.