

View Online at <https://aerobasegroup.com/nsn/5340-01-299-5943>

**Cross Sectional Shape:**

Flat

**Width:**

8.000 inches

**Edge Shape:**

Rectangle, multi holes

**Length:**

21.470 inches

**Corner Radius:**

0.120 inches

**Hole Quantity Along Length:**

12

**Hole Quantity Along Width:**

9

**Distance Between Holes Along Length:**

3.031 inches and 2.625 inches and 3.375 inches and 2.937 inches

**Distance Between Holes Along Width:**

2.250 inches and 3.000 inches

**Distance From First Hole Centerline To End Along Length:**

0.220 inches

**Distance From First Hole Centerline To End Along Width:**

0.250 inches

**Body Thickness:**

1.900 inches

**Securing Device Type:**

Threaded fastener

**Mounting Opening Shape Style:**

Threaded hole

**End Application:**

Alq-135b countermeasure

**Features Provided:**

Special marking

**Special Features:**

Hole legend: a-e, 'a' diameter requires 0.138-32 unc 2b thd and is cbored 0.312 in., 'b' diameter 0.1885 to 0.1895 in. Thru, 'c' diameter is 0.103 to 0.105 in. & cbored 0.187 in. X 0.093 in. Dp; 'd' diameter is 0.1885 to 0.1895 in. & 0.156 dp, 'e' diameter is 0.220 in. & 0.156 in. Dp; item requires a cover frame p/n 151-002434-102, 3 locating bushings p/n 151-002434-103, bushings are of stainless steel cl 303, cond a per astm a 582 & passivated (e300) per mil-f-14072; also required is 6 fin stock of aluminum alloy 1100-0, qq-a-250/1, 0.006 in. Thk p/n 151-002434-104, & 2 bosses p/n 151-002434-105 boss lg 0.620 in., & 0.070 to 0.080 in. Thk

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-200/8 federal specification single material response or qq-a-250/11 federal specification single material response

**Surface Treatment:**

Primer and paint polyurethane

**Surface Treatment Specification:**

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531c0

**Mil-std (military Standard):**

Mil-p-23377 spec.