

View Online at <https://aerobasegroup.com/nsn/5340-01-300-8981>

Mounting Hole Type:

Plain and threaded

First Leg Length:

0.800 inches

Second Leg Length:

1.100 inches

Second Leg Width:

1.600 inches

First Leg Hole Diameter:

Between 0.155 inches and 0.157 inches

Second Leg Distance Between Hole Centers Along Width:

0.700 inches

Second Leg Distance Between Hole Centers Along Length:

0.420 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.848 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.252 inches

Second Leg Slot Length:

0.218 inches

Second Leg Slot Width:

0.156 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

3.730 inches

First Leg Distance Between Hole Centers Along Width:

0.364 inches

First Leg Distance Between Hole Centers Along Length:

0.090 inches

First Leg Distance From Edge To Hole Center Along Width:

1.180 inches

First Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Hole Arrangement Style:

Two holes

Second Leg Hole Arrangement Style:

2 slots

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

0.156 in. By 0.218 in. Slot two places first leg, 1.000 in. Distance between slot centers first leg; 0.155 in. Min and 0.157 in. Maximum hole diameter one place second leg and 0.312 in. Hole diameter one place second leg, 0.450 in. Distance between hole centers along w

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, cl 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.