

View Online at <https://aerobasegroup.com/nsn/5340-01-300-8981>

**Mounting Hole Type:**

Plain and threaded

**First Leg Length:**

0.800 inches

**Second Leg Length:**

1.100 inches

**Second Leg Width:**

1.600 inches

**First Leg Hole Diameter:**

Between 0.155 inches and 0.157 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.700 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.420 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.848 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.252 inches

**Second Leg Slot Length:**

0.218 inches

**Second Leg Slot Width:**

0.156 inches

**First Leg Thickness:**

0.090 inches

**Second Leg Thickness:**

0.090 inches

**First Leg Width:**

3.730 inches

**First Leg Distance Between Hole Centers Along Width:**

0.364 inches

**First Leg Distance Between Hole Centers Along Length:**

0.090 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.180 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.310 inches

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Hole Arrangement Style:**

2 slots

**Features Provided:**

Nut

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

0.156 in. By 0.218 in. Slot two places first leg, 1.000 in. Distance between slot centers first leg; 0.155 in. Min and 0.157 in. Maximum hole diameter one place second leg and 0.312 in. Hole diameter one place second leg, 0.450 in. Distance between hole centers along w

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8, h32 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2, cl 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.