NSN 5340-01-301-2046 Webbing Strap - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5340-01-301-2046 |
|--|
| Width: |
| Between 3.000 inches and 3.500 inches |
| Length: |
| 122.450 inches |
| Environmental Protection: |
| Heat resistant and light resistant and resin impregnated resistant |
| Loop Style Designator: |
| Delta |
| End Type: |
| Both w/attachments |
| Buckle Material: |
| Steel |
| Buckle Surface Treatment: |
| Zinc, astm b633, type 2, class fe/zn13 or cadmium, qq-p-416, type 2, class 2 |
| Buckle Location: |
| Located in middle |
| Fastened Buckle Feature: |
| ncluded |
| Buckle Fastening Method: |
| Sewed |
| Loop Material: |
| Steel |
| Fastened Loop Feature: |
| ncluded |
| Loop Fastening Method: |
| Sewed |
| Loop Location: |
| Location both ends |
| End Attachment/fastening Facility: |
| Loop |
| Buckle Style Designator: |
| Ratchet |
| Color: |
| Olive drab |
| Material: |
| Nylon, mil-w-25361, type 2 and nylon, mil-w-4088, type 9 |
| Material: |
| Plastic polyethylene terephthalate and plastic polyhexamethylene adipamide |
| Material Specification: |
| Mil-w-25361, type 2 military specification 1st material response and mil-w-4088, type 9 military specification 2nd material response |
| Shelf Life: |

N/a

NSN 5340-01-301-2046

Webbing Strap - Page 2 of 2



| | | • - | | | | | | |
|---|-----|-----|----|-----|----|----|----|----|
| | In | | Of | RЛ | മാ | CI | ır | Δ. |
| L | ,,, | | | IVI | ca | | | |

--

Demilitarization:

No

Fiig:

T372-b

Mil-std (military Standard):

Mil-w-25361 spec.