

View Online at <https://aerobasegroup.com/nsn/5340-01-301-7885>

Mounting Hole Type:

Plain

First Leg Length:

1.500 inches

Second Leg Length:

1.500 inches

Second Leg Width:

2.500 inches

First Leg Slot Length:

1.500 inches

First Leg Slot Width:

0.250 inches

Second Leg Hole Diameter:

0.660 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.620 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

2.500 inches

First Leg End Width:

2.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.620 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

135.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Special Features:

Cadmium plate, qq-p-416, type 2, cl 3; harden to rockwell c26 through c30

Material:

Steel comp 4130 or steel comp 4140

Material Specification:

Qq-s-626 federal specification 1st material response or qq-s-626 federal specification 2nd material response or mil-s-18729 military specification 2nd material response

Surface Treatment:

Paint

Surface Treatment Specification:

12350824, para 3.1, u.S. Army tank-automotive command mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-s-18729 spec.