

View Online at <https://aerobasegroup.com/nsn/5340-01-302-5973>

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.1793 inches

**Second Leg Length:**

2.440 inches

**Second Leg Width:**

14.500 inches

**First Leg Hole Diameter:**

0.406 inches

**Second Leg Hole Diameter:**

0.406 inches

**Second Leg Distance Between Hole Centers Along Width:**

12.875 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

3.875 inches

**Second Leg Distance Between Second And Third Hole Centers Along Width:**

3.875 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.555 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Thickness:**

0.1793 inches

**Second Leg Thickness:**

0.1793 inches

**Center Section Height:**

1.4993 inches

**Center Section Width:**

14.500 inches

**Center Section Thickness:**

0.1793 inches

**First Leg Width:**

14.500 inches

**First Leg Distance Between Hole Centers Along Width:**

5.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.750 inches

**First Leg Style:**

Cut out

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**First Leg Cutout Length:**

1.030 inches

**First Leg Cutout Width:**

1.440 inches

**Material:**

Steel comp 1009 or steel comp 1137 or steel uns k01507

**Material Specification:**

Astm a569 assn standard 1st material response or astm a109 assn standard 2nd material response or astm a109 assn standard 3rd material response

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.