

View Online at <https://aerobasegroup.com/nsn/5340-01-302-5973>

Mounting Hole Type:

Plain

First Leg Length:

2.1793 inches

Second Leg Length:

2.440 inches

Second Leg Width:

14.500 inches

First Leg Hole Diameter:

0.406 inches

Second Leg Hole Diameter:

0.406 inches

Second Leg Distance Between Hole Centers Along Width:

12.875 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

3.875 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

3.875 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.555 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.1793 inches

Second Leg Thickness:

0.1793 inches

Center Section Height:

1.4993 inches

Center Section Width:

14.500 inches

Center Section Thickness:

0.1793 inches

First Leg Width:

14.500 inches

First Leg Distance Between Hole Centers Along Width:

5.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

First Leg Cutout Length:

1.030 inches

First Leg Cutout Width:

1.440 inches

Material:

Steel comp 1009 or steel comp 1137 or steel uns k01507

Material Specification:

Astm a569 assn standard 1st material response or astm a109 assn standard 2nd material response or astm a109 assn standard 3rd material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.