## NSN 5340-01-303-0012

Webbing Strap - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-303-0012

Width:
Between 1.625 inches and 1.813 inches
Length:
Between 70.000 inches and 74.000 inches
Environmental Protection:
Heat resistant and light resistant and resin impregnated resistant
End Type:
Both w/attachments
Ring Material:
Steel, aisi 4130
Buckle Material:
Aluminum alloy, 2024, t4
Buckle Location:
Located one end
Fastened Buckle Feature:
Included
Buckle Fastening Method:
Sewed
Ring Shape:
D and d-shape w/threaded stub
Fastened Ring Feature:
Included
Ring Fastening Method:
Sewed
Ring Location:
Located on both ends
End Attachment/fastening Facility:
Ring
Buckle Style Designator:
Tie down
Special Features:
Buckle located 28.000 in. Min 32.000 in. Maximum from one end and completely covered with felt
Color:
Olive drab, us army, 7
Material:
Nylon, mil-w-4088, type 10
Material:
Plastic polyhexamethylene adipamide
Material Specification:
Mil-w-4088, type 10 military specification single material response

Shelf Life: N/a

## NSN 5340-01-303-0012

Webbing Strap - Page 2 of 2



		• .					
	In	iŧ	Of	MAG	200		ω.
•	,,,	ıı	v.	IAIC	as	u	┏.

--

Demilitarization:

No

Fiig:

T372-b

Mil-std (military Standard):

Mil-w-4088 spec.