

View Online at <https://aerobasegroup.com/nsn/5340-01-303-0961>

Mounting Hole Type:

Plain

First Leg Length:

2.250 inches

Second Leg Length:

3.687 inches

Second Leg Width:

12.000 inches

First Leg Hole Diameter:

0.406 inches

Second Leg Hole Diameter:

0.406 inches

Second Leg Distance Between Hole Centers Along Width:

10.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

12.000 inches

First Leg Distance Between Hole Centers Along Width:

8.000 inches

First Leg Distance From Edge To Hole Center Along Width:

2.000 inches

First Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

122.0 degrees

Special Features:

Two additional holes, 0.875 in. Diameter on first leg; alternate matl steel, astm a36

Material:

Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023

Material Specification:

Astm a635 assn standard all material responses

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification 1st treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.