

View Online at <https://aerobasegroup.com/nsn/5340-01-303-1638>

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.125 inches

**Second Leg Width:**

3.000 inches

**First Leg Hole Diameter:**

0.281 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.124 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.438 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

2.000 inches

**Second Leg Slot Length:**

3.000 inches

**Second Leg Slot Width:**

0.218 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

3.000 inches

**First Leg Distance Between Hole Centers Along Width:**

1.750 inches

**First Leg Distance Between Hole Centers Along Length:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.625 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.625 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Four holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

103.0 degrees

**Special Features:**

Included 1 p/n 2823941-2 cagec 10001, strap retaining; aluminum alloy, qq-a-250/8; 1.000 in. Wd; 2.875 in. Lg; 2 mounting holes 0.218 in. Dia; 1.562 in. H; 1 p/n 2823941-1, aluminum alloy, qq-a-250/8; 1.000 in. Wd; 2.875 in. Lg; 2 mounting holes 0.218 in. Dia; 0.938 in. H; both parts painted per mil-w-3970 and mil-std-1303

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-250/11 federal specification single material response

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

Mil-w-3970 military specification single treatment response and 1303 military standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-w-3970 spec.