

View Online at <https://aerobasegroup.com/nsn/5340-01-303-1638>

Mounting Hole Type:

Plain

First Leg Length:

2.125 inches

Second Leg Width:

3.000 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Distance Between Hole Centers Along Width:

2.124 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.438 inches

Second Leg Distance From Edge To Hole Center Along Length:

2.000 inches

Second Leg Slot Length:

3.000 inches

Second Leg Slot Width:

0.218 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

3.000 inches

First Leg Distance Between Hole Centers Along Width:

1.750 inches

First Leg Distance Between Hole Centers Along Length:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.625 inches

First Leg Distance From Edge To Hole Center Along Length:

0.625 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

103.0 degrees

Special Features:

Included 1 p/n 2823941-2 cagec 10001, strap retaining; aluminum alloy, qq-a-250/8; 1.000 in. Wd; 2.875 in. Lg; 2 mounting holes 0.218 in. Dia; 1.562 in. H; 1 p/n 2823941-1, aluminum alloy, qq-a-250/8; 1.000 in. Wd; 2.875 in. Lg; 2 mounting holes 0.218 in. Dia; 0.938 in. H; both parts painted per mil-w-3970 and mil-std-1303

Material:

Aluminum alloy

Material Specification:

Qq-a-250/11 federal specification single material response

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-w-3970 military specification single treatment response and 1303 military standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-w-3970 spec.