

View Online at <https://aerobasegroup.com/nsn/5340-01-303-8666>

Mounting Hole Type:

Countersunk and plain

First Leg Length:

0.500 inches

Second Leg Length:

0.620 inches

Second Leg Width:

Between 0.220 inches and 0.280 inches

First Leg Hole Diameter:

Between 0.140 inches and 0.145 inches

Second Leg Hole Diameter:

Between 0.100 inches and 0.104 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.125 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.110 inches and 0.140 inches

First Leg Thickness:

Between 0.085 inches and 0.115 inches

Second Leg Thickness:

Between 0.085 inches and 0.115 inches

First Leg Width:

0.234 inches

First Leg Distance From Edge To Hole Center Along Width:

0.062 inches

First Leg Distance From Edge To Hole Center Along Length:

0.120 inches

First Leg End Radius:

0.120 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/8, t6 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.