

View Online at <https://aerobasegroup.com/nsn/5340-01-304-1817>

Mounting Hole Type:

Plain

First Leg Length:

3.000 inches

Second Leg Length:

5.380 inches

Second Leg Width:

4.880 inches

First Leg Slot Length:

1.500 inches

First Leg Slot Width:

0.437 inches

Second Leg Distance Between Hole Centers Along Width:

3.891 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.494 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.375 inches

Second Leg Slot Length:

Between 1.235 inches and 1.387 inches

Second Leg Slot Width:

Between 0.425 inches and 0.498 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

4.880 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.594 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.594 inches

First Leg Distance From Edge To Hole Center Along Width:

0.846 inches

First Leg Distance From Edge To Hole Center Along Length:

1.250 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

3 slots

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

106.85 degrees

Second Leg Cutout Length:

2.560 inches

Second Leg Cutout Width:

1.750 inches

Material:

Steel

Material Specification:

Astm a36 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0