

View Online at <https://aerobasegroup.com/nsn/5340-01-304-2921>

Mounting Hole Type:

Plain

First Leg Length:

1.400 inches

Second Leg Length:

2.200 inches

End Application:

Fire detection sys; c5a

Second Leg Width:

1.500 inches

First Leg Hole Diameter:

0.199 inches

Second Leg Distance Between Hole Centers Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.000 inches

Second Leg Slot Length:

0.438 inches

Second Leg Slot Width:

0.188 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

1.000 inches

First Leg Distance Between Hole Centers Along Width:

0.600 inches

First Leg Distance From Edge To Hole Center Along Width:

0.400 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Extended flat

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Left hand tube

Material:

Steel comp 304

Material Specification:

Astm a167, cond a assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type ii federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0