NSN 5340-01-304-2932

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-304-2932

| view Offilite at https://aerobasegroup.com/hsh/oo4o-o1-o04-2002 |
|--|
| Cross Sectional Shape: |
| Flat |
| Hole Diameter: |
| Between 0.098 inches and 0.102 inches |
| Width: |
| 4.135 inches |
| Edge Shape: |
| Rectangle, multi holes |
| Length: |
| 7.070 inches |
| Hole Quantity Along Length: |
| 4 |
| Hole Quantity Along Width: |
| 4 |
| Distance Between Holes Along Length: |
| 2.140 inches |
| Distance Between Holes Along Width: |
| 2.500 inches |
| Distance From First Hole Centerline To End Along Length: |
| 2.285 inches |
| Distance From First Hole Centerline To End Along Width: |
| 0.817 inches |
| Body Thickness: |
| 1.000 inches |
| Securing Device Type: |
| Threaded fastener |
| Mounting Opening Shape Style: |
| Unthreaded hole |
| End Application: |
| Lantirn navigation pod |
| Features Provided: |
| Special marking |
| Special Features: |
| Mtg holes require 0.112-40 unc-2bthds |
| Material: |
| Aluminum alloy 6061 |
| Material Specification: |
| Qq-a-250/11 federal specification single material response |
| Surface Treatment Specification: |
| Mil-c-5541, cl 1a military specification 1st treatment response and mil-p-23377 cl 2 military specification 2nd treatment response and |
| mil-c-22750 military specification 3rd treatment response |

N/a

Shelf Life:

NSN 5340-01-304-2932

Access Cover - Page 2 of 2



| | ι | Jn | it | Of | Measure: |
|--|---|----|----|----|----------|
|--|---|----|----|----|----------|

--

Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-c-5541 spec.