

View Online at <https://aerobasegroup.com/nsn/5340-01-304-9579>

Mounting Hole Type:

Plain and threaded

First Leg Length:

2.000 inches

Second Leg Length:

3.000 inches

Second Leg Width:

7.250 inches

First Leg Slot Length:

Between 0.750 inches and 0.810 inches

First Leg Slot Width:

Between 0.440 inches and 0.470 inches

Second Leg Hole Diameter:

0.375 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

2.875 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

2.875 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.130 inches

First Leg Thickness:

0.255 inches

Second Leg Thickness:

0.375 inches

First Leg Width:

7.250 inches

First Leg Distance Between First And Second Hole Centers Along Width:

2.875 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

2.875 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

3 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel or steel comp m1020

Material Specification:

Astm a36 assn standard 1st material response or astm a575 assn standard 2nd material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0