

View Online at <https://aerobasegroup.com/nsn/5340-01-305-4384>

**Mounting Hole Type:**

Threaded

**First Leg Length:**

0.240 inches

**Second Leg Length:**

0.330 inches

**Second Leg Width:**

0.280 inches

**First Leg Slot Length:**

0.370 inches

**First Leg Slot Width:**

Between 0.064 inches and 0.069 inches

**Second Leg Hole Diameter:**

0.060 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.157 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.210 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.078 inches

**First Leg Thickness:**

0.105 inches

**Second Leg Thickness:**

0.075 inches

**First Leg Width:**

0.585 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.225 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.122 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

First leg relieved 0.585 in. Lg by 0.190 in. W by 0.040 in. Dp; first leg inside radius 0.120 in. Second leg one corner chamfered 0.050 in. By 45.0 deg

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11, t6 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 3 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.