

View Online at <https://aerobasegroup.com/nsn/5340-01-305-9524>

Mounting Hole Type:

Plain and countersunk

First Leg Length:

Between 0.570 inches and 0.630 inches

Second Leg Length:

Between 1.020 inches and 1.080 inches

Second Leg Width:

Between 5.720 inches and 5.780 inches

First Leg Slot Length:

Between 0.243 inches and 0.257 inches

First Leg Slot Width:

Between 0.153 inches and 0.167 inches

First Leg Thickness:

0.062 inches

Second Leg Thickness:

0.062 inches

First Leg Width:

1.740 inches

First Leg Distance Between Hole Centers Along Width:

1.438 inches

First Leg Distance From Edge To Hole Center Along Width:

0.150 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Cutout Length:

Between 0.570 inches and 0.630 inches

First Leg Cutout Width:

1.140 inches

Special Features:

Second leg 7 countersunk mounting holes 0.115 in. Min and 0.125 in. Maximum dia, 8 countersunk mounting holes 0.095 in. Min and 0.101 in. Maximum dia, 1 slot 0.243 in. Min and 0.257 in. Maximum lg by 0.153 in. Min and 0.167 in. Maximum w; second leg extends above first leg by 0.450 in.

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 t6 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

171 military specification 4th treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

spec.