

View Online at <https://aerobasegroup.com/nsn/5340-01-305-9524>

**Mounting Hole Type:**

Plain and countersunk

**First Leg Length:**

Between 0.570 inches and 0.630 inches

**Second Leg Length:**

Between 1.020 inches and 1.080 inches

**Second Leg Width:**

Between 5.720 inches and 5.780 inches

**First Leg Slot Length:**

Between 0.243 inches and 0.257 inches

**First Leg Slot Width:**

Between 0.153 inches and 0.167 inches

**First Leg Thickness:**

0.062 inches

**Second Leg Thickness:**

0.062 inches

**First Leg Width:**

1.740 inches

**First Leg Distance Between Hole Centers Along Width:**

1.438 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.150 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Cut out

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Square

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**First Leg Cutout Length:**

Between 0.570 inches and 0.630 inches

**First Leg Cutout Width:**

1.140 inches

**Special Features:**

Second leg 7 countersunk mounting holes 0.115 in. Min and 0.125 in. Maximum dia, 8 countersunk mounting holes 0.095 in. Min and 0.101 in. Maximum dia, 1 slot 0.243 in. Min and 0.257 in. Maximum lg by 0.153 in. Min and 0.167 in. Maximum w; second leg extends above first leg by 0.450 in.

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 t6 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

171 military specification 4th treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

spec.