

View Online at <https://aerobasegroup.com/nsn/5340-01-306-4196>

Mounting Hole Type:

Plain

First Leg Length:

5.000 inches

Second Leg Length:

13.250 inches

Reinforcement Method (non-core):

Gusset center section

Second Leg Width:

3.000 inches

First Leg Slot Length:

0.880 inches

First Leg Slot Width:

0.440 inches

First Leg Thickness:

0.375 inches

Second Leg Thickness:

0.375 inches

First Leg Width:

3.000 inches

First Leg Distance Between Hole Centers Along Width:

Between 1.980 inches and 2.020 inches

First Leg Distance Between Hole Centers Along Length:

Between 2.980 inches and 3.020 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

4 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

No hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Gusset, 12.875 in. Lg, 5.000 in. H, 0.375 in. Thk, welded to center of both legs

Material:

Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp m1010 or steel comp m1012 or steel comp m1015 or steel comp m1017 or steel comp m1020

Surface Treatment:

Enamel

Surface Treatment Specification:

Tt-e-489 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0