

View Online at <https://aerobasegroup.com/nsn/5340-01-306-4196>

**Mounting Hole Type:**

Plain

**First Leg Length:**

5.000 inches

**Second Leg Length:**

13.250 inches

**Reinforcement Method (non-core):**

Gusset center section

**Second Leg Width:**

3.000 inches

**First Leg Slot Length:**

0.880 inches

**First Leg Slot Width:**

0.440 inches

**First Leg Thickness:**

0.375 inches

**Second Leg Thickness:**

0.375 inches

**First Leg Width:**

3.000 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 1.980 inches and 2.020 inches

**First Leg Distance Between Hole Centers Along Length:**

Between 2.980 inches and 3.020 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

4 slots

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

No hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Gusset, 12.875 in. Lg, 5.000 in. H, 0.375 in. Thk, welded to center of both legs

**Material:**

Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp m1010 or steel comp m1012 or steel comp m1015 or steel comp m1017 or steel comp m1020

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Tt-e-489 federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0