

View Online at <https://aerobasegroup.com/nsn/5340-01-306-4197>

Mounting Hole Type:

Plain and threaded

First Leg Length:

2.203 inches

Second Leg Length:

5.200 inches

Second Leg Width:

30.000 inches

First Leg Slot Length:

1.250 inches

First Leg Slot Width:

0.750 inches

Second Leg Hole Diameter:

0.500 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

12.500 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

12.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

2.500 inches

First Leg Thickness:

0.750 inches

Second Leg Thickness:

0.880 inches

Center Section Height:

3.238 inches

Center Section Width:

30.000 inches

Center Section Thickness:

0.700 inches

First Leg Width:

30.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

11.500 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

11.500 inches

First Leg Distance From Edge To Hole Center Along Width:

3.505 inches

First Leg Distance From Edge To Hole Center Along Length:

0.828 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

3 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

One hole 0.375-16 unc-2b located on second leg

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-200/4, 5083 federal specification 1st material response or qq-a-200/5, 5086 federal specification 2nd material response or qq-a-250/6, 5083 federal specification 1st material response or qq-a-250/7 h32 federal specification 2nd material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0