NSN 5340-01-306-4197

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-306-4197

Mounting Hole Type:
Plain and threaded
First Leg Length:
2.203 inches
Second Leg Length:
5.200 inches
Second Leg Width:
30.000 inches
First Leg Slot Length:
1.250 inches
First Leg Slot Width:
0.750 inches
Second Leg Hole Diameter:
0.500 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
12.500 inches
Second Leg Distance Between Second And Third Hole Centers Along Width:
12.500 inches
Second Leg Distance From Edge To Hole Center Along Width:
2.500 inches
First Leg Thickness:
0.750 inches
Second Leg Thickness:
0.880 inches
Center Section Height:
3.238 inches
Center Section Width:
30.000 inches
Center Section Thickness:
0.700 inches
First Leg Width:
30.000 inches
First Leg Distance Between First And Second Hole Centers Along Width:
11.500 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
11.500 inches
First Leg Distance From Edge To Hole Center Along Width:
3.505 inches
First Leg Distance From Edge To Hole Center Along Length:
0.828 inches
First Leg Style:
Square
Oqualo

NSN 5340-01-306-4197

Double Angle Bracket - Page 2 of 2



First Leg Hole Arrangement Style:
3 slots
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Three holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Special Features:
One hole 0.375-16 unc-2b located on second leg
Material:
Aluminum alloy 5083 or aluminum alloy 5086
Material Specification:
Qq-a-200/4, 5083 federal specification 1st material response or qq-a-200/5, 5086 federal specification 2nd material response or qq-a-250/6,
5083 federal specification 1st material response or qq-a-250/7 h32 federal specification 2nd material response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A042a0