NSN 5340-01-306-9064

Double Angle Bracket - Page 1 of 2

Material:

Aluminum alloy 5052



View Online at https://aerobasegroup.com/nsn/5340-01-306-9064

| Mounting Hole Type: |
|---|
| Countersunk and plain |
| First Leg Length: |
| 1.750 inches |
| Second Leg Length: |
| 1.750 inches |
| First Leg Hole Diameter: |
| 0.234 inches |
| First Leg Thickness: |
| 0.063 inches |
| Second Leg Thickness: |
| 0.063 inches |
| Center Section Height: |
| 2.520 inches |
| Center Section Width: |
| 1.750 inches |
| Center Section Thickness: |
| 0.063 inches |
| First Leg Width: |
| 1.000 inches |
| First Leg Distance Between Hole Centers Along Length: |
| 0.750 inches |
| First Leg Distance From Edge To Hole Center Along Width: |
| 0.500 inches |
| First Leg Distance From Edge To Hole Center Along Length: |
| 0.500 inches |
| First Leg Style: |
| Square |
| First Leg Hole Arrangement Style: |
| Two holes |
| Features Provided: |
| Nut |
| Second Leg Relationship To First Leg: |
| Identical |
| First Leg Angle: |
| 90.0 degrees |
| Second Leg Angle: |
| 90.0 degrees |
| Special Features: |
| F4 additional countersunk holes each leg 0.098 in. Min and 0.101 in. Maximum dia; 1 hole in center section 1.031 in. Diameter and 4 holes |
| 0.125 in. Diameter cuntersunk to 0.225 in. Min and 0.240 in. Maximum by 100 deg |

NSN 5340-01-306-9064

Double Angle Bracket - Page 2 of 2

Fiig: A042a0



| Material Specification: |
|---|
| Qq-a-250/8, h34 federal specification single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, class 2, type 2 federal specification single treatment response |
| Style Designator: |
| Adjacent angles |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |