## NSN 5340-01-307-9443

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-307-9443
Mounting Hole Type:
Threaded
First Leg Length:
Between 1.120 inches and 1.160 inches
Second Leg Length:
Between 1.120 inches and 1.160 inches
First Leg Hole Diameter:
0.190 inches
First Leg Thickness:
0.300 inches
Second Leg Thickness:
0.300 inches
Center Section Height:
Between 5.185 inches and 5.215 inches
Center Section Width:
0.500 inches
Center Section Thickness:
Between 0.380 inches and 0.420 inches
First Leg Width:
0.500 inches
First Leg Distance From Edge To Hole Center Along Width:
0.250 inches
First Leg Distance From Edge To Hole Center Along Length:
0.300 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
One hole
Second Leg Relationship To First Leg:
Identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Special Features:
First and second leg w/thd mtg holes 0.190-32unf-2b w/cbore 0.250 diameter by 0.135 in. Dp and csk 0.395 in. Diameter by 82 degrees
located on outer faces of legs; three thd mtg holes in center leg 0.112-40unc-2b through located on longitudinal centerline and centered
w/1.500 in. Between mtg centers; 0.030 in. Bend radius two places; color 23538, fed-std-595; incl chromate finish, mil-c-5541, cl 1a and
primer, epoxy, mil-p-85582
Material:

**Surface Treatment:** 

Diagtic polyurothan

Aluminum alloy 6061

**Material Specification:** 

Qq-a-250/11, t651 federal specification single material response

## NSN 5340-01-307-9443

Double Angle Bracket - Page 2 of 2



Surface Treatment Specification:
Mil-c-83286 military specification single treatment response
Style Designator:
Adjacent angles
Shelf Life:
N/a

**Unit Of Measure:** 

Demilitarization:

No Fiig:

A042a0

Mil-std (military Standard):

Mil-c-83286 spec.