## NSN 5340-01-308-5422

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-308-5422

Cross Sectional Shape:
Flat
Hole Diameter:
Between 0.420 inches and 0.427 inches
Width:
5.000 inches
Edge Shape:
Rectangle, multi holes
Length:
11.960 inches
Hole Quantity Along Length:
4
Hole Quantity Along Width:
8
Distance Between Holes Along Length:
2.000 inches
Distance Between Holes Along Width:
3.300 inches
Distance From First Hole Centerline To End Along Length:
0.980 inches
Distance From First Hole Centerline To End Along Width:
Distance From First Hole Centerline To End Along Width:  0.850 inches
0.850 inches
0.850 inches  Body Thickness:
0.850 inches  Body Thickness: 0.090 inches
0.850 inches  Body Thickness: 0.090 inches  Securing Device Type:
0.850 inches  Body Thickness: 0.090 inches  Securing Device Type:  Special
0.850 inches  Body Thickness: 0.090 inches  Securing Device Type:  Special  Mounting Opening Shape Style:
0.850 inches  Body Thickness: 0.090 inches  Securing Device Type: Special  Mounting Opening Shape Style: Unthreaded hole
0.850 inches  Body Thickness: 0.090 inches  Securing Device Type: Special  Mounting Opening Shape Style: Unthreaded hole  End Application:
0.850 inches  Body Thickness: 0.090 inches  Securing Device Type: Special  Mounting Opening Shape Style: Unthreaded hole End Application: An/alq-131
0.850 inches  Body Thickness: 0.090 inches  Securing Device Type: Special  Mounting Opening Shape Style: Unthreaded hole End Application: An/alq-131 Features Provided:
0.850 inches  Body Thickness: 0.090 inches  Securing Device Type: Special  Mounting Opening Shape Style: Unthreaded hole  End Application: An/alq-131  Features Provided: Special marking
0.850 inches  Body Thickness: 0.090 inches  Securing Device Type: Special  Mounting Opening Shape Style: Unthreaded hole End Application: An/alq-131 Features Provided: Special marking Special Features:
0.850 inches  Body Thickness: 0.090 inches  Securing Device Type: Special  Mounting Opening Shape Style: Unthreaded hole  End Application: An/alq-131  Features Provided: Special marking  Special Features: All holes are cbored 0.620 in. Plus 0.020 in. Dia, 0.055 in. Dp far side
Body Thickness: 0.090 inches Securing Device Type: Special Mounting Opening Shape Style: Unthreaded hole End Application: An/alq-131 Features Provided: Special marking Special Features: All holes are cbored 0.620 in. Plus 0.020 in. Dia, 0.055 in. Dp far side Material:
0.850 inches  Body Thickness: 0.090 inches  Securing Device Type: Special  Mounting Opening Shape Style: Unthreaded hole End Application: An/alq-131 Features Provided: Special marking Special Features: All holes are cbored 0.620 in. Plus 0.020 in. Dia, 0.055 in. Dp far side  Material: Aluminum alloy 6061
Body Thickness: 0.090 inches Securing Device Type: Special Mounting Opening Shape Style: Unthreaded hole End Application: An/alq-131 Features Provided: Special marking Special Features: All holes are cbored 0.620 in. Plus 0.020 in. Dia, 0.055 in. Dp far side Material: Aluminum alloy 6061 Material Specification:

**Surface Treatment Specification:** 

Mil-p-23377 type i per mil-f-18264 military specification 1st treatment response

## NSN 5340-01-308-5422

Access Cover - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A531c0	

Mil-std (military Standard):

Mil-p-23377 spec.

Shelf Life: