

View Online at <https://aerobasegroup.com/nsn/5340-01-308-6083>

Mounting Hole Type:

Plain

First Leg Length:

1.375 inches

Second Leg Length:

2.000 inches

Second Leg Width:

12.000 inches

Second Leg Hole Diameter:

0.563 inches

Second Leg Distance Between Hole Centers Along Width:

Between 10.484 inches and 10.516 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

Between 3.484 inches and 3.516 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

3.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.313 inches

First Leg Thickness:

1.125 inches

Second Leg Thickness:

0.562 inches

First Leg Width:

12.000 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

First leg chamfered 0.625 in. By 45.0 degrees along two interior underside edges; mtg holes in second leg continue through the thickness of the first leg

Material:

Steel

Material Specification:

Astm a304-79 assn standard single material response

Surface Treatment:

Enamel semigloss and phosphate and primer

Surface Treatment Specification:

Tt-e-529 federal specification 1st treatment response and tt-c-490 federal specification 2nd treatment response and tt-p-664 federal specification 3rd treatment response or mil-p-53030 military specification 4th treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-p-53030 spec.