NSN 5340-01-309-4358

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-309-4358 **Mounting Hole Type:** Plain First Leg Length: 3.500 inches Second Leg Length: 6.000 inches Reinforcement Method (non-core): Gusset both legs Second Leg Width: 16.875 inches First Leg Hole Diameter: 0.688 inches Second Leg Hole Diameter: 0.812 inches Second Leg Distance Between First And Second Hole Centers Along Width: 6.938 inches Second Leg Distance Between Second And Third Hole Centers Along Width: 6.938 inches Second Leg Distance From Edge To Hole Center Along Width: 1.500 inches Second Leg Distance From Edge To Hole Center Along Length: 1.562 inches First Leg Thickness: 0.500 inches **Second Leg Thickness:** 0.500 inches First Leg Width: 16.875 inches First Leg Distance Between Hole Centers Along Width: 13.875 inches First Leg Distance From Edge To Hole Center Along Width: First Leg Distance From Edge To Hole Center Along Length: 1.000 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square

Second Leg Hole Arrangement Style: Three holes

NSN 5340-01-309-4358

Angle Bracket - Page 2 of 2



| Features Provided: |
|------------------------------------------------------------------|
| Nut |
| Second Leg Relationship To First Leg: |
| Not identical |
| First Leg Angle: |
| 90.0 degrees |
| Special Features: |
| Includes two spacers, p/n 11671591 |
| Material: |
| Steel |
| Material Specification: |
| Mil-s-13281 cl a military specification single material response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A042a0 |
| Mil-std (military Standard): |
| Mil-s-13281 spec. |