## NSN 5340-01-309-4360

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-309-4360

Marinting Hala Times
Mounting Hole Type:
Plain
First Leg Length:
1.670 inches
Second Leg Length:
6.220 inches
Second Leg Width:
2.780 inches
First Leg Hole Diameter:
0.281 inches
Second Leg Hole Diameter:
0.156 inches
Second Leg Distance Between Hole Centers Along Length:
5.100 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.230 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.560 inches
Second Leg Distance Between First And Second Hole Centers Along Length:
1.830 inches
Second Leg Distance Between Second And Third Hole Centers Along Length:
1.440 inches
First Leg Thickness:
0.130 inches
Second Leg Thickness:
0.130 inches
Center Section Height:
1.750 inches
Center Section Width:
2.780 inches
Center Section Thickness:
0.130 inches
First Leg Width:
2.780 inches
First Leg Distance Between Hole Centers Along Width:
1.125 inches
First Leg Distance From Edge To Hole Center Along Width:
0.828 inches
First Leg Distance From Edge To Hole Center Along Length:
0.290 inches
First Leg Style:
Square

## NSN 5340-01-309-4360

Double Angle Bracket - Page 2 of 2



First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Four holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Special Features:
Color black; additional holes second leg: 1 rectangular hole 1.000 in. Lg by 0.800 in. W, 1 center countersunk hole 0.199 in. Dia, 2 left side
holes 0.156 in. Dia
Material:
Aluminum alloy 5052
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2, class 2 military specification single treatment response
Style Designator:
Adjacent angles
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-a-8625 spec.