

View Online at <https://aerobasegroup.com/nsn/5340-01-309-4360>

Mounting Hole Type:

Plain

First Leg Length:

1.670 inches

Second Leg Length:

6.220 inches

Second Leg Width:

2.780 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Hole Diameter:

0.156 inches

Second Leg Distance Between Hole Centers Along Length:

5.100 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.230 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.560 inches

Second Leg Distance Between First And Second Hole Centers Along Length:

1.830 inches

Second Leg Distance Between Second And Third Hole Centers Along Length:

1.440 inches

First Leg Thickness:

0.130 inches

Second Leg Thickness:

0.130 inches

Center Section Height:

1.750 inches

Center Section Width:

2.780 inches

Center Section Thickness:

0.130 inches

First Leg Width:

2.780 inches

First Leg Distance Between Hole Centers Along Width:

1.125 inches

First Leg Distance From Edge To Hole Center Along Width:

0.828 inches

First Leg Distance From Edge To Hole Center Along Length:

0.290 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Color black; additional holes second leg: 1 rectangular hole 1.000 in. Lg by 0.800 in. W, 1 center countersunk hole 0.199 in. Dia, 2 left side holes 0.156 in. Dia

Material:

Aluminum alloy 5052

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, class 2 military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.