

View Online at <https://aerobasegroup.com/nsn/5340-01-309-7782>

Mounting Hole Type:

Plain

First Leg Length:

2.240 inches

Second Leg Length:

2.250 inches

Second Leg Width:

4.500 inches

First Leg Hole Diameter:

0.312 inches

Second Leg Distance Between Hole Centers Along Width:

3.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

Second Leg Slot Length:

0.531 inches

Second Leg Slot Width:

0.750 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

4.500 inches

First Leg Distance Between Hole Centers Along Width:

1.750 inches

First Leg Distance From Edge To Hole Center Along Width:

1.375 inches

First Leg Distance From Edge To Hole Center Along Length:

1.120 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

Special Features:

Color green

Material:

Steel comp 1020 or steel comp 1009 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1008 or steel comp 1010

Material Specification:

Qq-s-635 federal specification 1st material response or qq-s-635 federal specification 2nd material response or astm a635 assn standard all material responses

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.