

View Online at <https://aerobasegroup.com/nsn/5340-01-310-2385>

Mounting Hole Type:

Plain

First Leg Length:

0.750 inches

Second Leg Length:

1.500 inches

Second Leg Width:

3.000 inches

First Leg Hole Diameter:

Between 0.193 inches and 0.199 inches

Second Leg Hole Diameter:

Between 0.388 inches and 0.392 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

3.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.000 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Pself-locking stud, 720s-312st, precision metal products co, pressed into 0.388 in. Min 0.392 in. Maximum diameter hole located 1.120 in. From rear edge and 1.500 in. From either side edge; stud thd 0.250-20unc-2a; material cres

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h34 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 3, cl1, clear military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.