

View Online at <https://aerobasegroup.com/nsn/5340-01-310-2385>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.750 inches

**Second Leg Length:**

1.500 inches

**Second Leg Width:**

3.000 inches

**First Leg Hole Diameter:**

Between 0.193 inches and 0.199 inches

**Second Leg Hole Diameter:**

Between 0.388 inches and 0.392 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.380 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

3.000 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

1.000 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Pself-locking stud, 720s-312st, precision metal products co, pressed into 0.388 in. Min 0.392 in. Maximum diameter hole located 1.120 in. From rear edge and 1.500 in. From either side edge; stud thd 0.250-20unc-2a; material cres

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8, h34 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 3, cl1, clear military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.