

View Online at <https://aerobasegroup.com/nsn/5340-01-310-7067>

Mounting Hole Type:

Countersunk and plain

First Leg Length:

1.500 inches

Second Leg Length:

3.190 inches

Second Leg Width:

3.500 inches

First Leg Hole Diameter:

Between 0.438 inches and 0.500 inches

Second Leg Hole Diameter:

Between 0.438 inches and 0.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.630 inches

First Leg Thickness:

1.880 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

3.500 inches

First Leg Distance Between Hole Centers Along Width:

2.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.625 inches

First Leg Distance From Edge To Hole Center Along Length:

0.935 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

One additional hole located along edge of first leg, 0.380 in. Min and 0.416 in. Maximum dia, 0.620 in. Deep

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-200/4 h111 federal specification 1st material response or qq-a-250/6 h321 federal specification 1st material response or qq-a-200/5 h111 federal specification 2nd material response or qq-a-250/7 h32 federal specification 2nd material response

Surface Treatment:

Plastic epoxy and plastic polyamide

Surface Treatment Specification:

Mil-c-22750 type 1 military specification all treatment responses

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-22750 spec.