

View Online at <https://aerobasegroup.com/nsn/5340-01-310-7067>

**Mounting Hole Type:**

Countersunk and plain

**First Leg Length:**

1.500 inches

**Second Leg Length:**

3.190 inches

**Second Leg Width:**

3.500 inches

**First Leg Hole Diameter:**

Between 0.438 inches and 0.500 inches

**Second Leg Hole Diameter:**

Between 0.438 inches and 0.500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.750 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.630 inches

**First Leg Thickness:**

1.880 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

3.500 inches

**First Leg Distance Between Hole Centers Along Width:**

2.250 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.625 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.935 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

One additional hole located along edge of first leg, 0.380 in. Min and 0.416 in. Maximum dia, 0.620 in. Deep

**Material:**

Aluminum alloy 5083 or aluminum alloy 5086

**Material Specification:**

Qq-a-200/4 h111 federal specification 1st material response or qq-a-250/6 h321 federal specification 1st material response or qq-a-200/5 h111 federal specification 2nd material response or qq-a-250/7 h32 federal specification 2nd material response

**Surface Treatment:**

Plastic epoxy and plastic polyamide

**Surface Treatment Specification:**

Mil-c-22750 type 1 military specification all treatment responses

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-22750 spec.