

View Online at <https://aerobasegroup.com/nsn/5340-01-312-4977>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 0.730 inches and 0.770 inches

**Second Leg Length:**

1.000 inches

**Second Leg Width:**

1.500 inches

**Second Leg Corner Radius:**

0.220 inches

**First Leg Hole Diameter:**

Between 0.220 inches and 0.230 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**Center Section Height:**

Between 0.570 inches and 0.690 inches

**Center Section Width:**

1.500 inches

**Center Section Thickness:**

0.063 inches

**First Leg Width:**

1.500 inches

**First Leg Corner Radius:**

0.220 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 0.990 inches and 1.010 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

No hole

**Features Provided:**

Nut

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Special Features:**

Righthand nut position

**Material:**

Aluminum alloy 2024 and aluminum alloy 1230

**Material Specification:**

Qq-a-250/5, t3 federal specification single material response

**Surface Treatment:**

Plastic epoxy and plastic polyamide

**Surface Treatment Specification:**

Mil-p-23377 military specification single treatment response

**Style Designator:**

Adjacent angles

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-p-23377 spec.