
NSN 5340-01-312-4977

Double Angle Bracket - Page 1 of 2





Mounting Hole Type: Plain First Leg Length: Between 0.730 inches and 0.770 inches Second Leg Length: 1.000 inches Second Leg Width: 1.500 inches Second Leg Corner Radius: 0.220 inches First Leg Hole Diameter: Between 0.220 inches and 0.230 inches **First Leg Thickness:** 0.063 inches Second Leg Thickness: 0.063 inches **Center Section Height:** Between 0.570 inches and 0.690 inches **Center Section Width:** 1.500 inches **Center Section Thickness:** 0.063 inches First Leg Width: 1.500 inches First Leg Corner Radius: 0.220 inches First Leg Distance Between Hole Centers Along Width: Between 0.990 inches and 1.010 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.240 inches and 0.260 inches First Leg Distance From Edge To Hole Center Along Length: 0.250 inches First Leg Style: Corner radius First Leg Hole Arrangement Style: Two holes Second Leg Style: Corner radius Second Leg Hole Arrangement Style: No hole **Features Provided:** Nut

NSN 5340-01-312-4977

Double Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Rigth hand nut position

Material:

Aluminum alloy 2024 and aluminum alloy 1230

Material Specification:

Qq-a-250/5, t3 federal specification single material response

Surface Treatment:

Plastic epoxy and plastic polyamide

Surface Treatment Specification:

Mil-p-23377 military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-p-23377 spec.