

View Online at <https://aerobasegroup.com/nsn/5340-01-314-4950>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.467 inches

**Second Leg Length:**

2.060 inches

**Second Leg Width:**

5.530 inches

**First Leg Hole Diameter:**

0.116 inches

**Second Leg Hole Diameter:**

0.128 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

1.800 inches

**Second Leg Distance Between Second And Third Hole Centers Along Width:**

1.800 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.300 inches

**First Leg Thickness:**

0.090 inches

**Second Leg Thickness:**

0.090 inches

**First Leg Width:**

5.530 inches

**First Leg Distance Between Hole Centers Along Width:**

3.600 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.312 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.312 inches

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Color iridescent yellow; 2 additional holes 1st leg 0.128 in. Dia; 2 additional horizontal holes 2nd leg 0.250 in. Dia; 2 vertical holes 2nd leg 0.156 in. Dia

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8 h34 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, class 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.