

View Online at <https://aerobasegroup.com/nsn/5340-01-315-0253>

Mounting Hole Type:

Plain and threaded

First Leg Length:

1.500 inches

Second Leg Length:

1.660 inches

End Application:

Electric; lantern mobile shelter set

Second Leg Width:

2.380 inches

Second Leg End Width:

2.100 inches

First Leg Hole Diameter:

Between 0.220 inches and 0.226 inches

Second Leg Hole Diameter:

0.223 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.190 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.040 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

2.380 inches

First Leg End Width:

2.100 inches

First Leg Distance Between Hole Centers Along Width:

1.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.280 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.19 radians

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

2ng leg has a self locking nut per mil-n-45938/7

Material:

Aluminum alloy 5052 or aluminum alloy 6061

Material Specification:

Qq-a-250/8, h32 federal specification single material response or qq-a-250/11, t4 federal specification single material response

Style Designator:

Angle

Fsc Application Data:

Power strip

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0