

View Online at <https://aerobasegroup.com/nsn/5340-01-316-1507>

**Mounting Hole Type:**

Counterbored and plain

**First Leg Length:**

1.780 inches

**Second Leg Length:**

3.120 inches

**Second Leg Width:**

1.250 inches

**First Leg Hole Diameter:**

0.344 inches

**Second Leg Hole Diameter:**

0.406 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.620 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

1.250 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.620 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg End Radius:**

0.690 inches

**Second Leg End Radius:**

0.690 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

Between 81.0 degrees and 85.0 degrees

**Second Leg Offset Angle:**

Between 17.0 degrees and 21.0 degrees

**Special Features:**

Rh usage; opposite of p/n 12342135

**Material:**

Aluminum alloy 6063

**Material Specification:**

Qq-a-200/9 t4 federal specification single material response or astm b221 t4 assn standard single material response

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

**Style Designator:**

Offset angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.